Visualize a published system sheet

FNP system

FNP number : 1141

Index FNP : S005

Last publication : 2025/05/07

State : PUBLISHED

Supplier : JOTUN

Total thickness : 300 µm

public comment EN : 25/02/2025 : Modification of Technical Datasheet according to CCTR 91C031 revision 10. ------ April 29th, 2022 : First publication of the system This system meets the EDF requirements for "PMUC" approval and has obtained a EUROCLASS B-s1,d0 fire reaction test classification. As indicated on the technical datasheet, the JOTATEMP 250 product is suitable for a temperature range from cryogenic -196°C to high temperature up to +650°C, on insulated and non-insulated surfaces ¤¤¤¤¤¤¤¤¤ WARNING ¤¤¤¤¤¤¤¤¤ This system obtained an unfavorable toxicological opinion linked to the presence of ethylbenzene - in application for EDF S.A. only. Pay attention to the risk of exposure to mists/aerosols in the event of spraying, and the risk of exposure to dust in the event of intervention on the dry product. ¤¤¤¤¤¤¤¤¤¤¤¤¤¤¤¤¤¤

Utilities type : PARC NUCLEAIRE

Technical sheet : FT EN 1141 Rev 4 23 01 2025.pdf

Codifications published

Série	Groupe
PEA/EEA PEB/EEB PEC/EEC PED	200
PEA/EEA PEB/EEB PEC/EEC PED	204
PEA/EEA PEB/EEB PEC/EEC PED	205
PEA/EEA PEB/EEB PEC/EEC PED	209
PEA/EEA PEB/EEB PEC/EEC PED	216

Coat list

Coat number	Product name	Thickness	Nature of the binder	Type of phase	Proportion of solvent
1	JOTATEMP 1000	150 µm	Matrice polymérique inerte (céramique)	SV	15
2	JOTATEMP 1000	150 µm	Matrice polymérique inerte (céramique)	SV	15
3	-=-=-=-=-=-=-=-=-=-=-				
4	JOTUN THINNER N° 7				